



SAFETY SHEET

FILAMENT | NYLON ULTRA

V 1.0 | 01-2016

VOLUMIC
IMPRIMANTES 3D

Safety Data Sheet according to Regulation (EC) N°1907/2006

SECTION 1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

Product:
Filament imprimante 3D - Nylon Ultra

Company:
VOLUMIC 3D
12bis Rue Louis GARNERAY
06300 NICE
France
Tel : +33 9 500 27 400

SECTION 2. HAZARDS IDENTIFICATION

No hazardous according to EC-Regulations

SECTION 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Polyamide, additives (wax and/or dyes) and spinfoinish

SECTION 4. FIRST-AID MEASURES

On contact with eyes:
Product is solid. Remove as any foreign object.

On skin contact:
Cool skin rapidly with cold water after contact with molten material.
Do not peel polymer from skin. Get medical attention, if necessary.

If inhaled:
Product is solid. No special measures required

On ingestion:
No special measures required

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: water, foam, carbon dioxide or dry powder.
Use self containing breathing apparatus for fire fighting in closed rooms.
At temperatures of > 300°C can be emitted: carbon monoxide and traces of other toxic substances, due to decomposition and oxidation of the product.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:
Particular danger of slipping on spilled product

Environmental precautions:
No special measures required

Methods and material for containment and cleaning up:
Collect mechanically.

SECTION 7. HANDLING AND STORAGE

Handling:
when handling carton boxes or pallets observe ergonomic recommendations



SAFETY SHEET

FILAMENT | NYLON ULTRA

V 1.0 | 01-2016

VOLUMIC
IMPRIMANTES 3D

Storage:
no special hazards, when storing carton boxes or pallets take measures against falling down.

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Personal protective equipment:

Respiratory protection:
Fine-dust mask, depending on application

Hand protection:
Protective gloves are recommended

Eye protection:
Safety glasses are recommended

Hygiene measures:
Wash hands before breaks and after work.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Filament
Melting point / melting range: 196 - 220 °C
Flash point: > 400 °C
Density: 1.12 – 1.15 g/cm³ at 20 °C
Water solubility: insoluble

SECTION 10. STABILITY AND REACTIVITY

Thermal decomposition: above 300 °C

SECTION 11. TOXICOLOGICAL INFORMATION

Non hazardous polymer. Special ingredients: the product may contain up to 0.3% finish. To date proper use of the monofilament has not been associated with any detrimental effect on health. Finish is applied as a processing aid and can generally be removed in an aqueous medium if so required.
May cause mechanical irritation.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity: The product does not affect on environment negatively, non-toxic
Persistence and degradability: Product to be inert and non-degradable.

SECTION 13. DISPOSAL CONSIDERATIONS

If recycling is not possible, the product must be taken to a waste disposal site or incinerated subject to local regulations.

SECTION 14. TRANSPORT INFORMATION

Road, marine or air transport: Non-hazardous goods

SECTION 15. REGULATORY INFORMATION

Hazard symbols, R or S phrases: none



SAFETY SHEET FILAMENT | NYLON ULTRA

V 1.0 | 01-2016

VOLUMIC
IMPRIMANTES 3D

SECTION 16. OTHER INFORMATION

This information is based on our present state of knowledge and does not guarantee specific properties of the products described or their suitability for a particular application.

VOLUMIC 3D
12bis Rue Louis GA RNERAY
06300 NICE
France

TVA: FR55452187792
EORI: FR45218779200026

Téléphone: +33 9 500 27 400
Email: info@volumic3d.com
Internet: www.volumic3d.com