



SAFETY SHEET

FILAMENT | PURGE ULTRA

V 1.0 | 20-10-2019

VOLUMIC
IMPRIMANTES 3D

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Product name: Purge Filament

Description: Thermoplastic

Revision date: October 20, 2019.

Contact for Information/Manufacturer identification:

VOLUMIC 3D

12bis Rue Louis GARNERAY

06300 NICE – France

Telephone: +33 9 500 27 400

Email: info@volumic3d.com

Internet: www.volumic3d.com

SECTION 2 HAZARDS IDENTIFICATION

2.1 EMERGENCY OVERVIEW

NFPA: Health 0, Flammability 0, Reactivity 0

2.2 OSHA REGULATORY STATUS

All Ingredients are encapsulated by the polymer and not considered hazardous by the OSHA Hazards Communication Standard (29 CFR 1910.1200).

2.3 POTENTIAL HEALTH EFFECTS

Routes of entry for solids include eye and skin contact, ingestion and inhalation.
Refer to section 4 for First Aid Measures

2.4 POTENTIAL ENVIRONMENTAL EFFECTS

None Known.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

This product does not contain chemicals that are considered Hazardous under OSHA 29 CFR 1910.1200

SECTION 4 FIRST AID MEASURES

Eyes: Flush with water. If irritation persists seek medical attention.

Skin: For thermal burns, immediately flush with cold water. Do not attempt to remove polymer from skin. Seek medical attention.

Inhalation: Leave exposed area and seek fresh air. If irritation persists seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention.

SECTION 5 FIRE FIGHTING MEASURES

Wear protective clothing and use self-contained breathing equipment. Extinguishing media to include water, foam, CO2 and dry chemical.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Spilled material may cause a slip hazard. Vacuum or sweep material and place in a disposal container.

SECTION 7 HANDLING AND STORAGE

Handling: See 8.3 personal Protective Equipment

Storage: Keep container closed to prevent contamination.



SAFETY SHEET FILAMENT | PURGE ULTRA

V 1.0 | 20-10-2019

VOLUMIC
IMPRIMANTES 3D

SECTION 8 EXPOSURE GUIDELINES

8.1 THIS PRODUCT DOES NOT CONTAIN CHEMICALS THAT ARE CONSIDERED HAZARDOUS UNDER OSHA 29 CFR 1910.1200

Special characteristics or information: No special characteristics listed for this product.

8.2 ENGINEERED CONTROLS

Localized ventilation is recommended.

8.3 PERSONAL PROTECTIVE EQUIPMENT

Eyes: Safety Glasses

Hands: Cotton gloves for handling molten plastic. Wear latex, nitrile or plastic gloves to avoid contamination of hand oils to the Purge Filament itself.

Skin: Protective clothing for contact with molten plastic.

Respirator: Not required for 3D printing as product is stable.

Hygiene: Wash thoroughly after handling and before eating or drinking.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical condition: Solid Pellets

Odor: Odorless at ambient temperature. Characteristic plastic odor during heating.

Melting Point Temp: 190°C

Flash Point Temp: 340°C

Auto Ignition Temp: 380°C

Flammability (solid, gaseous): Not reasonably applicable.

Min Limit of Explosion: Not reasonably applicable.

Max limit of Explosion: Not reasonably applicable.

Vapor pressure: Not reasonably applicable.

Relative density: 0.5 – 1.5 g / ml.

Bulk density: No data available.

pH Value: Not reasonably applicable.

VOC Content: Less than 5 parts per million.

Off-gassing: Does not occur until temperatures in excess of 380°C are reached. Well beyond typical processing conditions. Less than 0.01% of ash on complete combustion and the only gas produced is carbon dioxide. Does not meet the definition of a hazardous material as given in 29 CFR Part 1910.000 (OSHA).

SECTION 10 STABILITY AND REACTIVITY

This product is stable and non-reactive. Hazardous decomposition of products can occur if overheated beyond 380°C or ignited.

SECTION 11 TOXICOLOGY INFORMATION

Based on our experience and the information available, no adverse health effected are expected if handled as recommended with suitable precautions for designated uses.

SECTION 12 ECOLOGICAL INFORMATION

Refer to Section 6.

SECTION 13 DISPOSAL CONSIDERATIONS

Preferred options for disposal are (1) recycling, (2) incineration with energy recovery, (3) landfill. Treatment, storage, transportation and disposal must be in accordance with applicable State/Provincial and Local regulations.



SAFETY SHEET FILAMENT | PURGE ULTRA

V 1.0 | 20-10-2019

VOLUMIC
IMPRIMANTES 3D

SECTION 14 TRANSPORTATION INFORMATION

This product is not regulated under the following regulations:

- United State Department of Transportation (DOT)
- United States Coast Guard regulations.
- International Maritime Organization (IMO) regulations.
- International Civil Aviation Organization (ICAO) regulations.
- International Air Reports Association (IATA) regulations.
- Canadian Transportation of Dangerous Goods (TDG) regulations.
- European Agreement Concerning the International Carriage of Dangerous Good by Road (ADR) regulations.
- European Agreement Concerning the International Carriage of Dangerous Good by Rail (RID) regulations.
- Australian Dangerous Goods (ADG) regulations.

SECTION 15 REGULATORY INFORMATION

Reference Section 3

SARA Title III reporting: Not Required.

SECTION 16 OTHER INFORMATION

Definitions :

- CAS = Chemical Abstract Number
- DSL = Domestic Substance List
- OSHA = Occupational Safety and Health Act.
- PEL = Permissible Exposure Limit
- TSCA = Toxic Substance Control Act
- SARA = Superfund Amendments & Reclamation Act
- VOC = Volatile Organic Chemical
- N/E = Not Established.

These test results are based on reliable procedures. Due to variable conditions of fitness for a particular or methods of processing no guarantees or warranties are expected or implied including warranty of fitness for a particular purpose. These are not product specifications, nor manufacturing minimums. Each user of the material should make appropriate tests to determine the suitability of the material for use.

VOLUMIC 3D
12bis Rue Louis GA RNERAY
06300 NICE
France

TVA: FR55452187792
EORI: FR45218779200026

Phone: +33 9 500 27 400
Email: info@volumic3d.com
Internet: www.volumic3d.com